

KIRBY VERTICAL MIXER

ELP607 - ELP836



**EVEN MIX
FROM
START TO
FINISH**



INC.
Kirby
MANUFACTURING

CONTACT KIRBY AT
KIRBYMFG.COM OR BY
PHONE AT (209) 723-0778

VERTICAL MIXER FEATURES AND OPTIONS



TWO SPEED COOLER



ELECTRIC SHIFT



HYDRAULIC HOOKUPS



MULTIPLE DISCHARGE LENGTHS

Our Vertical ELP Mixers save you energy with low energy demand while creating an excellent mix with a constant discharge. The ELP Series keeps the TMR the same on the first cow as it is on the last.

Regardless of the feed, Kirby mixers are designed with 6 serrated knives per auger for optimal low power demand performance and can be fitted with a wide array of industry leading options. Also, the ELP Series is designed with a low profile to make loading as easy as possible.

Isn't it time you got everything you needed?

MODEL ELP607 - ELP836 SPECIFICATIONS

(ALL MEASUREMENTS IN INCHES)

Capacity (w/o belting)	607 TO 836
Overall Height	106-128
Overall Length	283
Overall Width	102
Discharge Height	32
Conveyor Width	30
Door Opening	42
Sidewall Thickness	1/4
Floor Thickness	3/4
PTO Requirements	540/1000 RPM
Minimum HP Requirement	80HP*

STANDARD FEATURES

- 3/4" Thick Auger Flighting
- Up to (6) Knives per Auger
- Heavy Duty Conveyor Chain
- Heavy Duty Single Axle w/22.5 Tires
- Adjustable Hitch w/ HD Landing
- Two Rotational Hay Stops
- L.H. Discharge Conveyor
- Observation Ladder
- Side Door Discharge

OPTIONAL FEATURES

- Weigh System (Scalehead & Load Cells)
- 12 ga. Stainless Steel Lined Walls (21") and Floor
- Stainless Steel Crossfeed Conveyor
- 12" Slide Discharge Conveyor
- Righthand, Lefthand or Dual Discharge
- Dog Leg Conveyor
- 10" Top Belting
- Hydraulic Rear Discharge Door
- 2-Speed Gear Box with Cable, Electric or Hydraulic shift in tractor

* HP requirements may vary depending on commodities



**CONTACT KIRBY AT
KIRBYMFG.COM OR BY
PHONE AT (209) 723-0778**

