

KIRBY VERTICAL MIXER

TRAILER MOUNTED 800 - 1400



**EVEN MIX
FROM
START TO
FINISH**



Kirby INC.
MANUFACTURING

CONTACT KIRBY AT
KIRBYMFG.COM OR BY
PHONE AT (209) 723-0778

VERTICAL MIXER FEATURES AND OPTIONS



RUBBER EXTENSION



CROSSFEED DISCHARGE



WALKING BEAM SUSPENSION



TWO SPEED COOLER



GREASED TENSIONER



SIDE DOOR



HYDRAULIC HOOKUPS



STEERABLE AXLE

Since 1946, Kirby has been obsessed with great products and great service. Our Vertical Mixers exemplify this commitment from end to end, creating a product that keeps the TMR the same on the first cow as it is on the last.

Isn't it time you got everything you needed?

MODEL LP 800 - 1400 SPECIFICATIONS

(ALL MEASUREMENTS IN INCHES)

| | |
|------------------------|--------------------------------|
| Capacity (w/o belting) | 835 CU/FT TO 1400 CU/FT |
| Overall Height | 113 TO 156 |
| Overall Length | 323 |
| Overall Width | 119 |
| Discharge Height | 32 |
| Conveyor Width | 36 |
| Door Opening | 51 |
| Sidewall Thickness | 1/4 |
| Floor Thickness | 1 |
| PTO Requirements | 1000 RPM |
| Minimum HP Requirement | 125 - 200 HP |

* Height (w/o belting & tandem axles)

** HP requirements many vary depending on commodities

STANDARD FEATURES

- 3/4" Thick Auger Flighting
- Seven Knives per Auger / Nine knives on 1400
- Hydraulic Front Discharge Door
- Heavy Duty Conveyor Chain
- Heavy Duty Single Axle
- Adjustable Hitch w/ HD Landing
- Two Rotational Hay Stops
- Scale and Mixer Installation
- L.H. Discharge Conveyor
- Observation Ladder

OPTIONAL FEATURES

- Weigh System (Scalehead & Load Cells)
- Stainless Steel Lined Walls and Floor
- Stainless Steel Crossfeed Conveyor
- 18" Slide Discharge Conveyor
- Righthand, Lefthand or Dual Discharge
- 10" Top Belting
- Hydraulic Rear Discharge Door
- 2-Speed Gear Box with Cable, Electric or Hydraulic shift / Automatic Shift on Fly
- Tandem Axles / Stearable Axle and Walking Beam



**CONTACT KIRBY AT
KIRBYMFG.COM OR BY
PHONE AT (209) 723-0778**

